
E-BREZZA

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455152T
Rev. 02 dated 06/09/2018

Name	E-BREZZA
Description	Decorative finish made of a printable paste enriched with natural fibres
Product characteristics	E-BREZZA is a printable decorative stucco for interiors and exteriors, whose natural fibres make it possible to create even thick material effects. E-BREZZA may be used to achieve different effects depending on the application technique used and the tool employed.
VOC Classification (Volatile organic compounds) Directive 2004/42/EC	Coatings for mineral substrate exterior walls EU VOC limit value for E-BREZZA (cat. A/c): 40 g/L (2010). E-BREZZA contains no more than 40 g/L of VOC.
IAQ Class (Indoor Air Quality)	
Produced in	MADE IN ITALY
Main application tools	Steel trowel, decorative tools as desired (rollers, brushes, spatulas, pads).
Application method	The surface must be uniform, matured, absorbent and free of patches or plastic finishes. In case, clean the surface well, removing all traces of previous paint and/or plaster, dirt, grease etc., by brushing, sanding or with cleaning equipment. Apply a coat of PRYMER ACQ in case of chalky surfaces. Render, if necessary, with STUCCO FONDO (interior Only) and let it cure. Apply 2 coats of E-BREZZA. It is possible to finish the application with 1 or more coats (depending on the desired effect) of VIERO VEL.
Practical tips	<p>Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts. The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.</p> <p>Environmental conditions -> temperature: min. + 5 °C/max. + 35 °C, relative humidity: < 75%. Primer conditions -> temperature: min. + 5 °C/max. + 35 °C, humidity: < 10 with respect to relative humidity.</p> <p>Shake the product before use or, if it is very dense, use a spatula or a mixing drill to achieve a workable consistency.</p> <p>When applying to very large surfaces be sure to interrupt the application in appropriate places (for example near drainpipes) or building joints. Do not rework on the same surface.</p> <p>After exterior applications, surfaces should be protected against driving rain, freezing temperatures (temp > 5 °C), fog, dew, and dust for at least 48 hours.</p> <p>It is recommended that the colour of the completely dried product be checked before application. Do not interrupt application in the middle of a wall.</p> <p>The product may not be stored for more than 48 hours after dilution.</p> <p>Rinse used tools with water immediately after use.</p> <p>Keep the paint can sealed and away from freezing temperatures and sunlight.</p>
Safety precautions	Safety information for users is contained in the relative safety data sheet. Empty containers or containers with traces of dried product film should be disposed of according to local regulations.

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

E-BREZZA

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455152T
Rev. 02 dated 06/09/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can Finish appearance		Paste Matt
Density g/ml	UNI 8910	1,50 ÷ 1,55
Brookfield Viscosity cPs	ASTM D 2196	Paste
Natural spread rate for effect creation (Kg/m ²)	ISO 7254	2.5 ÷ 3.0
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154.	24 months
Dry to touch Hours (h)		After 3
Hard dry Hours (h)		24
Overcoating Hours (h)		24
Application places		Interiors/Exteriors
Base + achievable colours		White + E-Brezza colour collection
Binder		Acrylic styrene
Tool cleaning		Water
Spatula application Dilution % by volume		Ready to use

FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



cromology
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424