
FONDO FORTE

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455155T
Rev. 02 dated 06/09/2018

Name	FONDO FORTE
Description	Adhesive primer for thick finishes
Product characteristics	FONDOFORTE is a universal grey paste primer specially formulated to optimize the adhesion of thick decorative products. FONDOFORTE reduces the absorbent power of the support material and renders it uniform, it is also extremely adhesive on smooth surfaces.
IAQ Class (Indoor Air Quality)	
Produced in	MADE IN ITALY
Main application tools	Steel spatula or sponge roller
Achievable effects	Clean thoroughly, removing dust, dirt, and any loose plaster fragments. Ensure that the wall is perfectly dry and, on highly absorbent or porous surfaces, apply a coat of PRYMER ALTA PENETRAZIONE to render the surface smooth and uniform. Apply FONDO FORTE (using a steel spatula) or sponge roller. Wait 24 hours before applying a decorative product.
Application method	
Practical tips	<p>Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts. The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.</p> <p>Environmental conditions -> temperature: min. + 5 °C/max. + 35 °C, relative humidity: < 75%. Primer conditions -> temperature: min. + 5 °C/max. + 35 °C, humidity: < 10 with respect to relative humidity.</p> <p>Shake the product before use or, if it is very dense, use a spatula or a mixing drill to achieve a workable consistency.</p> <p>After exterior applications, surfaces should be protected against driving rain, freezing temperatures (temp > 5 °C), fog, dew, and dust for at least 24 hours.</p> <p>Rinse used tools with water immediately after use.</p> <p>Keep the paint can sealed and away from freezing temperatures and sunlight.</p>
Safety precautions	Safety information for users is contained in the relative safety data sheet. Empty containers or containers with traces of dried product film should be disposed of according to local regulations.

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

FONDO FORTE

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455155T
Rev. 02 dated 06/09/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can Finish appearance		Paste Matt
Density g/ml	UNI 8910	1,50 ÷ 1,55
Brookfield Viscosity cPs	ASTM D 2196	20000 ÷ 28000
Natural spread rate with spatula application (kg/m ²)	ISO 7254	0,5
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154.	24 months
Dry to touch Hours (h)		Max.: 12
Hard dry Hours (h)		24
Overcoating Hours (h)		24
Application places		Interiors/Exteriors
Base + achievable colours		
Binder		Styrenic copolymer
Tool cleaning		Water
Application by roller or spatula Dilution % by volume		Ready to use

FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



CROMOLOGY
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424