

# Safety data sheet

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Code: VID455158S  
Product name: Multiquartz

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Wall paint

Identified Uses	Industrial	Professional	Consumer
Paint/Coating	-	-✓	-✓

### 1.3. Details of the supplier of the safety data sheet

Name: CROMOLOGY ITALIA SPA  
Full address: Sede Legale: Via IV Novembre, 4  
District and Country: 55016 Porcari LU  
ITALY  
Tel. 199119955 (+39)05832424  
Fax 199119977

e-mail address of the competent person responsible for the Safety Data Sheet: info-sds@cromology.it

Product distribution by: CROMOLOGY ITALIA SPA

### 1.4. Emergency telephone number

For urgent inquiries refer to Telephone numbers of the main Italian Anti-Poison Centers (active 24/24 hours):  
Centro Antiveleni di Pavia 0382 24444 (CAV Centro Nazionale di Informazione Tossicologica - Pavia); Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda - Milano); Centro Antiveleni di Bergamo 800 883300 (CAV Azienda Ospedaliera Papa Giovanni XXII - Bergamo); Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze); Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma); Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma); Centro Antiveleni Pediatrico di Roma 06 68593726 (CAVp Osp. Pediatrico Bambino Gesù- Roma); Centro Antiveleni di Foggia 0881 732326 (Azienda Ospedaliero Universitaria di Foggia); Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli).

For more information: Cromology Italia SpA 199119955 (+39)05832424  
From Monday to Friday 9:30-12:30 14:00-17:30.

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

Hazard classification and indication:

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH208**

Contains:

1,2-BENZOISOTIAZOL-3(2H)-ONE

2-METIL-2H-ISOTIAZOL-3-ONE

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

May produce an allergic reaction.

**EUH210**

Safety data sheet available on request.

Precautionary statements:

VOC (Directive 2004/42/EC) :

Matt coatings for interior walls and ceilings.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 30 (2010)

VOC of product : 30,00

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

### 3.1. Substances

Information not relevant

**SECTION 3. Composition/information on ingredients** ... / >>

**3.2. Mixtures**
**Contains:**
**Identification**                      **Conc. %**                      **Classification 1272/2008 (CLP)**
**Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)**

CAS      55965-84-9      0,00 - 0,0015      Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10

EC      611-341-5

INDEX      613-167-00-5

**2-(2-BUTOXYETHOXY)ETHANOL**

CAS      112-34-5      0,00 - 0,1      Eye Irrit. 2 H319

EC      203-961-6

INDEX      603-096-00-8

Reg. no.      01-2119475104-44-XXXX

**2-METIL-2H-ISOTIAZOL-3-ONE**

CAS      2682-20-4      0,00 - 0,1      Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC      220-239-6

**1,2-BENZOISOTIAZOL-3(2H)-ONE**

CAS      2634-33-5      0,00 - 0,05      Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

EC      220-120-9

INDEX      613-088-00-6

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures**
**4.1. Description of first aid measures**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

Information not available

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures**
**5.1. Extinguishing media**
**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

## SECTION 5. Firefighting measures ... / >>

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment.

Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Wash hands after use.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Store the containers sealed, in a well ventilated place, away from direct sunlight.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR		
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06
EU	OEL EU	Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	ACGIH RESP FRAC	
	ACGIH TOT DUST	
	TLV-ACGIH	ACGIH 2016
	TLV-TWA	

**Multiquartz**
**SECTION 8. Exposure controls/personal protection ... / >>**
**TITANIUM DIOXIDE**
**Threshold Limit Value**

Type	Country	TWA/8h mg/m <sup>3</sup>	ppm	STEL/15min mg/m <sup>3</sup>	ppm
TLV-ACGIH		10			
VLA	ESP	10			
VLEP	FRA	10			
WEL	GBR	4			
TLV	GRC		10		

**Predicted no-effect concentration - PNEC**

Normal value of STP microorganisms	100	mg/kg
Normal value in fresh water	>1	mg/l
Normal value for fresh water sediment	>1.000	mg/kg
Normal value in marine water	0,127	mg/l
Normal value for marine water sediment	>100	mg/kg
Normal value for the terrestrial compartment	>100	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				700 mg/kg p.c.				
Inhalation							10 mg/mc	

**1,2-PROPANEDIOL**
**Threshold Limit Value**

Type	Country	TWA/8h mg/m <sup>3</sup>	ppm	STEL/15min mg/m <sup>3</sup>	ppm
WEL	GBR	474	150		

**Predicted no-effect concentration - PNEC**

Normal value of STP microorganisms	20.000	mg/l
Normal value in fresh water	260	mg/l
Normal value for fresh water sediment	572	mg/kg
Normal value for marine water sediment	57,2	mg/kg
Normal value for the terrestrial compartment	50	mg/kg
Normal value for water, intermittent release	183	mg/l

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			50 mg/mc	10 mg/mc			168 mg/mc	10 mg/mc

**ALLUMINIO SILICATO DI SODIO E MAGNESIO**
**Threshold Limit Value**

Type	Country	TWA/8h mg/m <sup>3</sup>	ppm	STEL/15min mg/m <sup>3</sup>	ppm
ACGIH RESP FRAC		3			
ACGIH TOT DUST		10			

**SECTION 8. Exposure controls/personal protection ... / >>**
**SOLVENT NAPHTA (PETROLEUM), MEDIUM ALIPH.**
**Threshold Limit Value**

Type	Country	TWA/8h mg/m <sup>3</sup>	ppm	STEL/15min mg/m <sup>3</sup>	ppm
TLV-TWA		3			

**TALC**
**Threshold Limit Value**

Type	Country	TWA/8h mg/m <sup>3</sup>	ppm	STEL/15min mg/m <sup>3</sup>	ppm
TLV-ACGIH		2			
VLA	ESP	2			
WEL	GBR	1			
TLV	GRC		10		
OEL	NLD	0,25			

**2-(2-BUTOXYETHOXY)ETHANOL**
**Threshold Limit Value**

Type	Country	TWA/8h mg/m <sup>3</sup>	ppm	STEL/15min mg/m <sup>3</sup>	ppm
TLV-ACGIH		66	10		
AGW	DEU	67	10	100,5	15
MAK	DEU	67	10	100,5	15
VLA	ESP	67,5	10	101,2	15
TLV	GRC	67,5	10	101,2	15
VLEP	ITA	67,5	10	101,2	15
OEL	NLD	50		100	
VLE	PRT	67,5	10	101,2	15
OEL	EU	67,5	10	101,2	15

SKIN

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
 VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**
**2-(2-BUTOXYETHOXY)ETHANOL**
**2-(2-BUTOXYETHOXY)ETHANOL**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

**SECTION 8. Exposure controls/personal protection ... / >>**

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Appearance	Liquid
Colour	Various colours
Odour	Light, characteristic
Odour threshold	Not available
pH	8,5
Melting point / freezing point	Not available
Initial boiling point	> 100 °C
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,550 kg/l 20°C
Solubility	Dispersible in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	20000 mPa.s
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

VOC (Directive 2004/42/EC) : 30,00 g/litre



## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

### 2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

### 2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

### 10.5. Incompatible materials

### 2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

### 2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

## SECTION 11. Toxicological information

In the absence of experimental toxicological data on the product itself, the possible dangers of the product for health have been evaluated on the basis of the properties of the substances contained, according to the criteria provided for by the reference standard for classification. Consider therefore the concentration of the individual hazardous substances mentioned in section 3, to evaluate the toxicological effects deriving from exposure to the product.

### 11.1. Information on toxicological effects

### 2-(2-BUTOXYETHOXY)ETHANOL

**WORKERS:** inhalation; contact with the skin.

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

### ACUTE TOXICITY

**SECTION 11. Toxicological information** ... / >>

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component)  
LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component)  
LD50 (Oral) of the mixture: Not classified (no significant component)  
LD50 (Dermal) of the mixture: Not classified (no significant component)

**2-METIL-2H-ISOTIAZOL-3-ONE**

LD50 (Oral) >2.500 mg/kg Rat (OECD 423)  
LD50 (Dermal) >2.000 mg/kg Rat (OECD 402)  
LC50 (Inhalation) 5,71 mg/l/1h rat (OECD 403)

**2-(2-BUTOXYETHOXY)ETHANOL**

LD50 (Oral) 3.384 mg/kg Rat  
LD50 (Dermal) 2.700 mg/kg Rabbit

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

LD50 (Oral) 66 mg/kg Rat OECD 401  
LD50 (Dermal) >141 mg/kg Rat OECD 402

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

May produce an allergic reaction

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

**2-(2-BUTOXYETHOXY)ETHANOL**

**SECTION 12. Ecological information** ... / >>

**1,2-BENZOISOTIAZOL-3(2H)-ONE**

LC50 - for Fish	1,6 mg/l/96h Oncorhynchus mykiss (OECD 203)
EC50 - for Crustacea	3,27 mg/l/48h Daphnia magna (OECD 202)
EC50 - for Algae / Aquatic Plants	0,11 mg/l/72h Selenastrum capricornutum (OECD 201)

**2-METIL-2H-ISOTIAZOL-3-ONE**

LC50 - for Fish	6 mg/l/96h Oncorhynchus mykiss OECD 201
EC50 - for Crustacea	1,68 mg/l/48h Dafnia magna OECD 202
EC50 - for Algae / Aquatic Plants	0,157 mg/l/72h Pseudokirchneriella subcapitata (OECD 201)

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

LC50 - for Fish	0,22 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0,0052 mg/l/48h Dafnia magna
EC50 - for Algae / Aquatic Plants	0,048 mg/l/72h Pseudokirchneriella subcapitata

**12.2. Persistence and degradability**
**2-(2-BUTOXYETHOXY)ETHANOL**

Solubility in water 1000 - 10000 mg/l W12202

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

**12.3. Bioaccumulative potential**
**1,2-BENZOISOTIAZOL-3(2H)-ONE**

Partition coefficient: n-octanol/water 0,7 W122076,95

**2-METIL-2H-ISOTIAZOL-3-ONE**

Partition coefficient: n-octanol/water 0,32 W122073,16

**2-(2-BUTOXYETHOXY)ETHANOL**

Partition coefficient: n-octanol/water 1

Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one. [EC no. 220-239-6] (3:1)

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**
**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

### SECTION 13. Disposal considerations ... / >>

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Transport hazard class(es)

Not applicable

#### 14.4. Packing group

Not applicable

#### 14.5. Environmental hazards

Not applicable

#### 14.6. Special precautions for user

Not applicable

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Information not relevant

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation

1907/2006

None

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisation (Annex XIV REACH)

**SECTION 15. Regulatory information** ... / >>

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Matt coatings for interior walls and ceilings.

This product contains biocidal products

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 2</b>	Acute toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>H330</b>	Fatal if inhaled.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H302</b>	Harmful if swallowed.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH208</b>	Contains <name of sensitising substance>. May produce an allergic reaction.
<b>EUH210</b>	Safety data sheet available on request.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

**SECTION 16. Other information** ... / >>

- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

Note for users:

**SECTION 16. Other information** ... / >>

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.