
RUSTEN FINISH



www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455159T
Rev.01 dated 31/07/2018

Name	RUSTEN FINISH
Description	Mica-base finish for oxidized effects
Product characteristics	RUSTEN FINISH is a metallic enamel made from a special combination of micaceous iron particles. RUSTEN FINISH is perfect for reproducing the effect of oxidized metals.
VOC Classification (Volatile organic compounds) Directive 2004/42/EC	Single-component high performance coatings EU limit value for RUSTEN FINISH (Cat. A/i): 140 g/L (2010). RUSTEN FINISH contains no more than 140 g/L of VOC.
Produced in	MADE IN ITALY
Main application tools	Short-haired roller, steel spatula
Application method	Apply the product over Lithos
Practical tips	<p>Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts. The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.</p> <p>Environmental conditions -> temperature: min. + 5 °C/max. + 35 °C, relative humidity: < 75%. Primer conditions -> temperature: min. + 5 °C/max. + 35 °C, humidity: < 10 with respect to relative humidity.</p> <p>Shake the product before use or, if it is very dense, use a spatula or a mixing drill to achieve a workable consistency.</p> <p>When applying to very large surfaces be sure to interrupt the application in appropriate places (for example near drainpipes) or building joints. Do not rework on the same surface.</p> <p>After exterior applications, surfaces should be protected against driving rain, freezing temperatures (temp > 5 °C), fog, dew, and dust for at least 48 hours.</p> <p>It is recommended that the colour of the completely dried product be checked before application.</p> <p>Do not interrupt application in the middle of a wall.</p> <p>The product may not be stored for more than 48 hours after dilution.</p> <p>Rinse used tools with water immediately after use.</p> <p>Keep the paint can sealed and away from freezing temperatures and sunlight.</p>
Safety precautions	<p>Safety information for users is contained in the relative safety data sheet.</p> <p>Empty containers or containers with traces of dried product film should be disposed of according to local regulations.</p>

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

RUSTEN FINISH

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455159T
Rev.01 dated 31/07/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can		Liquid
Finish appearance		Micaceous
Density g/ml	UNI 8910	1,20 ÷ 1,29
Brookfield Viscosity cPs	ASTM D 2196	8000 ÷ 12000
Natural spread rate (lt/m ²)	ISO 7254	0.25 – 0.35
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154.	At least 24 months
Dry to touch Hours (h)		2
Hard dry Hours (h)		24
Overcoating Hours (h)		12 ÷ 18
Application places		Interiors
Base + achievable colours		Grey + Rusten colour collection
Binder		Acrylic-alkyd
Tool cleaning		Water
Dilution % by volume		Ready to use, Max. 5%

FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



cromology
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424