

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: VID455165S
Product name: Marmorin Hydro

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Painting product

Identified Uses	Industrial	Professional	Consumer
Paint/Coating	-	-✓	-✓

1.3. Details of the supplier of the safety data sheet

Name: CROMOLOGY ITALIA SPA
Full address: Sede Legale: Via IV Novembre, 4
District and Country: 55016 Porcari LU
ITALY
Tel. 199119955 (+39)05832424
Fax 199119977

e-mail address of the competent person responsible for the Safety Data Sheet: info-sds@cromology.it

Product distribution by: CROMOLOGY ITALIA SPA

1.4. Emergency telephone number

For urgent inquiries refer to Telephone numbers of the main Italian Anti-Poison Centers (active 24/24 hours):
Centro Antiveleni di Pavia 0382 24444 (CAV Centro Nazionale di Informazione Tossicologica - Pavia); Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca` Granda - Milano); Centro Antiveleni di Bergamo 800 883300 (CAV Azienda Ospedaliera Papa Giovanni XXII - Bergamo); Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze); Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma); Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma); Centro Antiveleni Pediatrico di Roma 06 68593726 (CAVp Osp. Pediatrico Bambino Gesù- Roma); Centro Antiveleni di Foggia 0881 732326 (Azienda Ospedaliero Universitaria di Foggia); Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli).

For more information: Cromology Italia SpA 199119955 (+39)05832424
From Monday to Friday 9:30-12:30 14:00-17:30.

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P280	Wear personal protective equipment / face protection.
P302+P352	IF ON SKIN: wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents / container in conformity with local regulation

Contains: CALCIUM HYDROXIDE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

SECTION 3. Composition/information on ingredients ... / >>**3.2. Mixtures****Contains:**

Identification	Conc. %	Classification 1272/2008 (CLP)
CALCIUM HYDROXIDE		
CAS	1305-62-0	24 - 28
EC	215-137-3	Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335
Reg. no.	01-2119475151-45-XXXX	

2-BROMO-2-NITROPROPAN-1,3-DIOL

CAS	52-51-7	0,00 - 0,1	Acute Tox. 4 H302, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1
EC	200-143-0		
INDEX	603-085-00-8		

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene.

If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Information not available

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from

draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment.

Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight.

Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
GBR		
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18

SECTION 8. Exposure controls/personal protection ... / >>

 OEL
 TLV-ACGIH ACGIH 2016

CALCIUM HYDROXIDE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
OEL		1		4	

Predicted no-effect concentration - PNEC

Normal value of STP microorganisms	3	mg/l
Normal value in fresh water	0,49	mg/l
Normal value in marine water	0,32	mg/l
Normal value for the terrestrial compartment	1.080	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	NEA	NPI	NEA	NPI				
Inhalation	4 mg/m ³	NPI	1 mg/m ³	NPI	4 mg/m ³	NPI	1 mg/m ³	NPI
Skin	VND	NPI	VND	NPI	VND	NPI	VND	NPI

CALCIUM CARBONATE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
TLV-ACGIH		10			
VLA	ESP	10			
WEL	GBR	4			
MAC	NLD	10			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
 VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

SECTION 8. Exposure controls/personal protection ... / >>
EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties
9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Various colours
Odour	Characteristic, light
Odour threshold	Not available
pH	>11,5
Melting point / freezing point	Not available
Initial boiling point	100 °C
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,600 kg/l 20°C
Solubility	Dispersible in water., Insoluble in hydrocarbon solvents.
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	>10000 mPa.s
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2004/42/EC) : 30,00 g/litre

SECTION 10. Stability and reactivity
10.1. Reactivity

Substances to avoid: acids. Conditions to avoid frost and strong heat. In case of dilution with water the product can be heated

2-BROMO-2-NITROPROPAN-1,3-DIOL

Decomposes on contact with: water, metals, strong bases.

SECTION 10. Stability and reactivity ... / >>

10.2. Chemical stability

The product is stable in normal conditions of use and storage. Avoid high temperatures can cause thermal decomposition

10.3. Possibility of hazardous reactions

See Section 10.1.

10.4. Conditions to avoid

Avoid the heating of the product

2-BROMO-2-NITROPROPAN-1,3-DIOL

Avoid exposure to: light, UV rays, moisture.

10.5. Incompatible materials

Acids

10.6. Hazardous decomposition products

Thermal decomposition or in case of fire gases can be released and potentially harmful to health.

2-BROMO-2-NITROPROPAN-1,3-DIOL

May develop: nitric oxide, carbon oxides, hydrobromic acid.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ACUTE TOXICITY

LC50 (Inhalation - vapours) of the mixture: Not classified (no significant component)

LC50 (Inhalation - mists / powders) of the mixture: Not classified (no significant component)

LD50 (Oral) of the mixture: Not classified (no significant component)

LD50 (Dermal) of the mixture: Not classified (no significant component)

CALCIUM HYDROXIDE

LD50 (Oral) >2.000 mg/kg Rat (OECD 425)

LD50 (Dermal) >25.000 mg/kg Rabbit (OECD 402)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

CALCIUM HYDROXIDE

LC50 - for Fish	>50,6 mg/l/96h Fish
LC50 - for Fish	50,6 mg/l pesci di acqua dolce.
EC50 - for Crustacea	>49,1 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	>184,57 mg/l/72h Algae

2-BROMO-2-NITROPROPAN-1,3-DIOL

LC50 - for Fish	20 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1,4 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,37 mg/l/72h

12.2. Persistence and degradability

2-BROMO-2-NITROPROPAN-1,3-DIOL

Solubility in water	286.000 mg/l W12202
---------------------	---------------------

12.3. Bioaccumulative potential

2-BROMO-2-NITROPROPAN-1,3-DIOL

Partition coefficient: n-octanol/water	0,22 W122073,16
--	-----------------

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation

1907/2006

Product

Point 3

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

SECTION 15. Regulatory information ... / >>

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Matt coatings for interior walls and ceilings.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 30 (2010)

VOC of product : 30,00

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation

SECTION 16. Other information ... / >>

- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.