
PRYMER ALTA PENETRAZIONE



www.vieropaints.com
info@vieropaints.it

Product data sheet VID455170T
Rev. 01 dated 03/08/2018

Name	PRYMER ALTA PENETRAZIONE
Description	Aqueous phase acrylic microemulsions-based undercoat reinforcing fixative
Product characteristics	<p>Excellent base reinforcing and coating power. Its ability to penetrate mineral substrates is similar to that of a solvent-based fixative. May be used to prevent streaking on façades. High alkalinity resistance. Particularly suitable for flaking exterior surfaces. May be overcoated with all aqueous phase organic finishes. Facilitates finish application. It is quick-drying and may be overcoated after a few hours. Application is fast, easy, and odourless.</p> <p>Applications</p> <ul style="list-style-type: none">• New and smooth, float finish wall surfaces, even if flaking.• Previously coated or partially deteriorated cement and cement-lime mortar surfaces, even if flaking.• Surfaces covered with old paint or mineral or synthetic coatings that adhere well to the base.
VOC Classification (Volatile organic compounds) Directive 2004/42/EC	<p>Fixing primers EU limit value for this product (Cat. A/h): 30 g/L (2010). PRYMER ALTA PENETRAZIONE contains no more than 30 g/L of VOC.</p>
Produced in	MADE IN ITALY
Main application tools	Brush
Achievable effects Application method	<p>For new surfaces: use a brush to remove dust and loose plaster fragments. Smooth out any imperfections (holes, cracks, fissures) with stucco or a smoothing agent that is suitable for the base. Sand and clean thoroughly. Shake the product and then apply one coat of PRYMER ALTA PENETRAZIONE.</p> <p>For previously painted surfaces: remove any loose paint or varnish. Smooth out any imperfections (holes, cracks, fissures) with stucco or a smoothing agent that is suitable for the base. Sand and clean thoroughly.</p> <p>If there is any algae or mould present, treat the surface with an anti-mould product. Shake the product and then apply one coat of PRYMER ALTA PENETRAZIONE.</p>
Practical tips	<p>Surface and environmental conditions: Temperature: min. + 5 °C/max. + 35 °C; Relative humidity : < 80%; Surface temperature: min. + 5 °C/max. + 35 °C; Surface humidity: < 10 with respect to relative humidity. Keep away from freezing temperatures. Do not apply on surfaces exposed to direct sunlight or strong wind. Wash and rinse tools after use.</p>
Safety precautions	<p>Keep the paint can sealed and away from freezing temperatures and sunlight. Safety information for users is contained in the relative safety sheet. Empty containers or containers with traces of dried product film should be disposed of according to local regulations.</p>

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

PRYMER ALTA PENETRAZIONE

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet VID455170T
Rev. 01 dated 03/08/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can Finish appearance		Slightly pigmented transparent liquid
Density g/ml	UNI 8910	1,02 ÷ 1,07
Brookfield Viscosity cPs	ASTM D 2196	1500 ÷ 2000
Natural spread rate (lt/m ²)	ISO 7254	7 ÷ 10 depending on the type, porosity, and condition of the wall
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154	At least 24 months
Dry to touch Hours (h)		1
Hard dry Hours (h)		4 ÷ 6
Overcoating Hours (h)		4 ÷ 6
Application places		Interiors/Exteriors
Colours		Pinkish - transparent
Tool cleaning		Water
Dilution % by volume		Ready to use

FOR PROFESSIONAL USE ONLY

Toll-free number: 800.219.420 (from Italy)
International assistance: +39.0583.2424 (from other countries)

Mon – Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



cromology
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424