
NATURWAX



www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455171T
Rev. 01 dated 31/07/2018

Name	NATURWAX
Description	Natural protective wax for spatulates and stuccos.
Product characteristics	NATURWAX is a natural wax-base protective coating that is ideal for lime putty-base decorative finishes. The NATURWAX formulation adds lustre and improves the water-repellence of the finish without significantly altering its breathability.
Produced in	MADE IN ITALY
Main application tools	Cloth, pad, trowel
Achievable effects	Apply a very thin single coat of NATURWAX using a cloth, pad, or trowel.
Application method	After the product is dry (12/24 hours), polish with a soft cloth or a low-speed orbital polisher. If the product is too fluid (typical during the summer), it should be thickened in the refrigerator or in a very cool place and mixed before use.
Practical tips	The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation. Environmental conditions -> temperature: min. + 5 °C/max. + 35 °C, relative humidity: < 75%. Primer conditions -> temperature: min. + 5 °C/max. + 35 °C, humidity: < 10 with respect to relative humidity. Shake the product before use or, if it is very dense, use a spatula to achieve a workable consistency. Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts. Excess material may cause non-uniform coating and/or whitish halos Rinse used tools with water immediately after use. Keep the paint can sealed and away from freezing temperatures and sunlight.
Safety precautions	Safety information for users is contained in the relative safety data sheet. Empty containers or containers with traces of dried product film should be disposed of according to local regulations.

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

NATURWAX

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455171T
Rev. 01 dated 31/07/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can Finish appearance		Paste Matt
Density g/ml	UNI 8910	0,87 ÷ 0,91
Brookfield Viscosity cPs	ASTM D 2196	Paste
Natural spread rate (lt/m ²)	ISO 7254	0,5 - 1
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154.	At least 24 months
Dry to touch Hours (h)		10
Hard dry Hours (h)		12 ÷ 24
Overcoating Hours (h)		12 ÷ 24
Application places		Interiors
Tool cleaning		Warm soapy water
Dilution % by volume		Ready to use Dilute with water if needed

FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



Cromology
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424