
SAPONIL



www.vieropaints.com

info@vieropaints.it

Product data sheet: VID455172T

Rev. 01 dated 31/07/2018

| | |
|---|--|
| Name | SAPONIL |
| Description | Soap-based water-repellent mattifying agent for finishes |
| Product characteristics | SAPONIL is a specially formulated protective agent used to render lime putty-based spatulated coatings water-repellent. SAPONIL reacts chemically and should therefore be applied to the finish while it is still fresh. SAPONIL does not form a film and does not hinder the breathability of the surface. |
| VOC Classification (Volatile organic compounds) Directive 2004/42/EC | Paint for decorative effects EU VOC limit value for Savonite Finishing (category A/I): 200 g/L (2010). Savonite Finitura contains no more than 200 g/L of VOC. |
| Produced in | MADE IN ITALY |
| Main application tools | Brush, trowel |
| Achievable effects | Apply to fresh lime putty-base finishes. |
| Application method | The product should be diluted at the moment of use with enough water to make it possible to apply with a brush. Apply a very thin single coat with a brush, and then press with a stainless steel trowel. |
| Practical tips | The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation. Environmental conditions -> temperature: min. + 5 °C/max. + 35 °C, relative humidity: < 75%. Primer conditions -> temperature: min. + 5 °C/max. + 35 °C, humidity: < 10 with respect to relative humidity. Shake the product before use or, if it is very dense, use a spatula to achieve a workable consistency. Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts. Excess material may cause non-uniform coating and/or whitish halos Rinse used tools with water immediately after use. Keep the paint can sealed and away from freezing temperatures and sunlight. |
| Safety precautions | Safety information for users is contained in the relative safety data sheet. Empty containers or containers with traces of dried product film should be disposed of according to local regulations. |

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

SAPONIL

Viero

www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455172T
Rev. 01 dated 31/07/2018

| TECHNICAL/REGULATORY INFORMATION | APPLICABLE REGULATION | INFO AT 20 °C AND 60% HUMIDITY |
|--|-----------------------|--|
| Appearance in the can | | Liquid |
| Finish appearance | | -- |
| Density g/ml | UNI 8910 | 0,6 ÷ 0,8 |
| Brookfield Viscosity cPs | ASTM D 2196 | 1700 ÷ 3000 |
| Natural spread rate (Kg/m ²) per coat | ISO 7254 | 0.05 - 0.10 |
| Flash point °C | UNI 8909 | Non-flammable |
| Shelf life (in a cool and dry place) | UNI 10154. | At least 24 months |
| Application places | | Interiors |
| Achievable colours (bases and pigments) | | Transparent |
| Tool cleaning | | Water |
| Dilution % by volume | | Dilute with water until solution may be applied by brush |

FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



CROMOLOGY
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424