

---

# STUCCO FONDO

---



www.vieropaints.com  
info@vieropaints.it

Product data sheet: VID455180T  
Rev. 01 dated 31/07/2018

<b>Name</b>	<b>STUCCO FONDO</b>
<b>Description</b>	Stucco paste
<b>Product characteristics</b>	STUCCO FONDO is a ready-to-use smoothing stucco paste for paint, mortar or gypsum plasters, as well as pre-fabricated concrete and cement elements.
<b>Produced in</b>	MADE IN ITALY
<b>Main application tools</b>	Spatula
<b>Achievable effects</b>	For new wall surfaces: clean thoroughly, removing all traces of dust and dirt. When applying on gypsum-base products. or on highly absorbent substrates, apply a coat of PRIMER ALTA PENETRAZIONE water-based fixative
<b>Application method</b>	<p>For partially deteriorated painted wall surfaces: completely remove loose, flaking or peeling parts. If necessary, stucco with STUCCO FONDO after reinforcing the part to be treated using PRIMER ALTA PENETRAZIONE water-based fixative. If needed, repeat the above steps to smooth out the surface.</p> <p>Ensure that the wall is perfectly dry and apply a coat of PRIMER ALTA PENETRAZIONE water-based fixative to the surface, and then wait until it is completely dry.</p> <p>Use a steel trowel to apply one or two coats of the product, depending on the type of surface to be treated. The second coat should only be applied after the first has completely dried.</p>
<b>Practical tips</b>	<p>The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.</p> <p>Environmental conditions -&gt; temperature: min. + 5 °C/max. + 35 °C, relative humidity: &lt; 75%.</p> <p>Primer conditions -&gt; temperature: min. + 5 °C/max. + 35 °C, humidity: &lt; 10 with respect to relative humidity.</p> <p>Shake the product before use or, if it is very dense, use a spatula to achieve a workable consistency.</p> <p>Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts.</p> <p>Rinse used tools with water immediately after use.</p> <p>Keep the paint can sealed and away from freezing temperatures and sunlight.</p>
<b>Safety precautions</b>	<p>Safety information for users is contained in the relative safety data sheet.</p> <p>Empty containers or containers with traces of dried product film should be disposed of according to local regulations.</p>

**FOR PROFESSIONAL USE ONLY**

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

**Viero is a trademark of Cromology Italia S.p.A.** - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

# STUCCO FONDO

# Viero

www.vieropaints.com  
info@vieropaints.it

Product data sheet: VID455180T  
Rev. 01 dated 31/07/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can Finish appearance		Paste Matt
Density g/ml	UNI 8910	1,7 ÷ 1,8
Brookfield Viscosity cPs	ASTM D 2196	Thixotropic
Natural spread rate (for 500-micron thickness) Kg/m <sup>2</sup>	ISO 7254	1,0
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154.	At least 24 months
Sanding Hours (h)		After 2
Hard dry Hours (h)		24
Overcoating Hours (h)		After 2
Application places		Interiors
Bases + achievable colours		White
Binder		Vinyl
Tool cleaning		Water
Dilution % by volume		Ready to use

## FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)  
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



**CROMOLOGY**  
Italia

COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =  
= ISO 14001 =  
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

**Viero is a trademark of Cromology Italia S.p.A.** - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424