
BITUME DECORATIVO



www.vieropaints.com
info@vieropaints.it

Product data sheet: VID455184T
Rev.01 dated 31/07/2018

Name	BITUME DECORATIVO
Description	Natural hydrocarbon powder for creating interior decorative effects
Product characteristics	BITUME DECORATIVO is a dark brown additive powder which creates an aged effect when added to finishes
Main application tools	Brush, spatula
Achievable effects Application method	PLEASE SEE THE APPLICATION MANUAL
Practical tips	<p>The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.</p> <p>Environmental conditions -> temperature: min. + 5 °C/max. + 35 °C, relative humidity: < 75%.</p> <p>Primer conditions -> temperature: min. + 5 °C/max. + 35 °C, humidity: < 10 with respect to relative humidity.</p> <p>Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts.</p> <p>The product may not be stored for more than 48 hours after dilution.</p> <p>Rinse used tools with water immediately after use.</p> <p>Keep the paint can sealed and away from freezing temperatures and sunlight.</p>
Safety precautions	<p>Safety information for users is contained in the relative safety data sheet.</p> <p>Empty containers or containers with traces of dried product film should be disposed of according to local regulations.</p>

FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

BITUME DECORATIVO

Product data sheet: VID455184T
Rev.01 dated 31/07/2018

TYPICAL PROPERTIES

SOFTENING POINT (R&B, Premelt Method)	300/315 °F (149/157 °C)	Particle Sizing % Retained
PENETRATION	0	+ 6 mesh 2 + 12 mesh 13
POWDER COLOUR	Brown	+ 20 mesh 18 + 50 mesh 33
SPECIFIC GRAVITY 77 °F (25 °C)	1.04 ÷ 1,10	+ 100 mesh 18 + 200 mesh 12 pan 4
FRACTURE LUSTRE	Bright	
STRUCTURE	Conchoidal	
FIXED CARBON	10 ÷ 15 %	
SULPHUR	0.3 %	
MOISTURE	0.5 %	
ASH	0.5 %	

FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



Cromology
Italia

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424